

# BeeLine Stump Grinders

BeeLine - Manual Push Stump Grinders - SGN Non Towable - SGT Towable  
Feature / Benefit / Comparison

## Benefits Key

**Safety** - a feature that provides a higher level of safety for the operator

**Perf ( Performance )** - a feature that improves performance - making it **Safer and Easier To Operate**

**Maint ( Maintenance )** - a feature that lowers labor and/or parts replacement costs

<u>Engine</u>	<b>Benefits</b>	<b>BeeLine 12/13hp</b>	<b>BeeLine 20/25hp</b>	<b>BeeLine 30hp</b>	Fill in 2nd choice	Fill in 3rd choice
12, 12.75 & 13hp	Match engine to job / budget	Yes				
20hp	Match engine to job / budget		Yes			
25hp	Match engine to job / budget		1st to Offer			
30hp	Match engine to job / budget			1st to Offer		
2 piece engine leveling wedge	Perf & Maint	1st to Offer	1st to Offer	1st to Offer		
<u>Cutter Wheel Drive Train</u>	<b>Benefits</b>	<b>BeeLine 12/13hp</b>	<b>BeeLine 20/25hp</b>	<b>BeeLine 30hp</b>	2nd choice	3rd choice
<u>Direct Drive</u>						
4 belt drive Power Band Cogged Belt	<b>Safety</b> Perf & Maint	Yes	Yes	Yes		
Self Adjusting Spring Loaded Belt Tensioner	<b>Safety</b> Perf & Maint	1st to Offer	1st to Offer	1st to Offer		
<u>Clutch Drive</u>						
Heavy duty commercial 3 groove centrifugal clutch	<b>Safety</b> Perf & Maint	1st to Offer	n/a	n/a		
3 belt drive Power Band Cogged Belt	<b>Safety</b> Perf & Maint	1st to Offer	n/a	n/a		
Self Adjusting Spring Loaded Belt Tensioner	<b>Safety</b> Perf & Maint	1st to Offer	1st to Offer	1st to Offer		
<u>Cutter Wheel</u>	<b>Benefits</b>	<b>BeeLine 12/13hp</b>	<b>BeeLine 20/25hp</b>	<b>BeeLine 30hp</b>	2nd choice	3rd choice
14" diameter, 3/8" thick, 16" cutting diameter	Perf & Maint	Yes	Yes	Yes		
8 individual 3 teeth in 1 Green Teeth	Perf & Maint	1st to Offer	1st to Offer	1st to Offer		
8 tooth cutter wheel acts like a ripping saw	Perf & Maint	Yes	Yes	Yes		

# BeeLine Stump Grinders

BeeLine - Manual Push Stump Grinders - SGN Non Towable - SGT Towable  
Feature / Benefit / Comparison

<b><u>Brakes</u></b>	<b>Benefits</b>	<b>BeeLine 12/13hp</b>	<b>BeeLine 20/25hp</b>	<b>BeeLine 30hp</b>	<b>Fill in 2nd choice</b>	<b>Fill in 3rd choice</b>
Dual brakes	<b>Safety</b> Perf & Maint	1st to Offer	1st to Offer	1st to Offer		
Heavy duty 1/4" angle iron brake bracket won't bend	<b>Safety</b> Perf & Maint	1st to Offer	1st to Offer	1st to Offer		
Heavy duty axle support	<b>Safety</b> Perf & Maint	1st to Offer	1st to Offer	1st to Offer		
Posi-Lock brake system. More control with less pressure	<b>Safety</b> Perf & Maint	1st to Offer	1st to Offer	1st to Offer		
<b><u>Non Towable Model</u></b>	<b>Benefits</b>	<b>BeeLine 12/13hp</b>	<b>BeeLine 20/25hp</b>	<b>BeeLine 30hp</b>	<b>2nd choice</b>	<b>3rd choice</b>
Taller Wider easier to operate 18-6.50x8 Turf Tires	<b>Safety</b> Perf	1st to Offer	1st to Offer	1st to Offer		
Width non towable	Specification	29.5	29.5	29.5		
<b><u>Towable Model</u></b>						
4:80x8 High Speed Trailer Tires	Specification	Yes	Yes	Yes		
Tow bar receiver an integral part of the frame	<b>Safety</b>	1st to Offer	1st to Offer	1st to Offer		
Width towable	Specification	31.5	31.5	31.5		
<b><u>Handle Bar &amp; Controls</u></b>	<b>Benefits</b>	<b>BeeLine 12/13hp</b>	<b>BeeLine 20/25hp</b>	<b>BeeLine 30hp</b>	<b>2nd choice</b>	<b>3rd choice</b>
8 position handle bar adjustment	<b>Safety</b> Perf	1st to Offer	1st to Offer	1st to Offer		
Longer handle bar arms	<b>Safety</b> Perf	1st to Offer	1st to Offer	1st to Offer		
Bi-Lingual English/Spanish Safety Decals standard	<b>Safety</b>	1st to Offer	1st to Offer	1st to Offer		
<b><u>General Information</u></b>	<b>Benefits</b>	<b>BeeLine 12/13hp</b>	<b>BeeLine 20/25hp</b>	<b>BeeLine 30hp</b>	<b>2nd choice</b>	<b>3rd choice</b>
Chips contained under frame	<b>Safety</b>	Yes	Yes	Yes		
Reinforced cutter wheel housing	Maint	1st to Offer	1st to Offer	1st to Offer		
Front & rear tie down point	<b>Safety</b>	1st to Offer	1st to Offer	1st to Offer		
Extended rear frame	<b>Safety</b>	Yes	Yes	Yes		
Height to top of engine	Specification	36.75 36.08	45.45	46.75		
Cutting Depth	Specification	18"	18"	18"		
Cutting Height	Specification	22.5"	22.5	22.5		
Cutting Diameter	Specification	no limit	no limit	no limit		
Weight	Specification	325	405	415		